store local data, such as temporary identifications. Optionally, the VLR of MSC **122** can be enhanced for more efficient co-ordination of GPRS and non-GPRS services and functionality (e.g. paging for circuit-switched calls which can be performed more efficiently via SGSN **126**, and combined GPRS and non-GPRS location updates).

[0040] Serving GPRS Support Node (SGSN) **126** is at the same hierarchical level as MSC **122** and keeps track of the individual locations of wireless devices **102**. SGSN **126** also performs security functions and access control. Gateway GPRS Support Node (GGSN) **128** provides internetworking with external packet-switched networks and is connected with SGSNs (such as SGSN **126**) via an IP-based GPRS backbone network. SGSN **126** performs authentication and cipher setting procedures based on the same algorithms, keys, and criteria as in existing GSM. In conventional operation, cell selection may be performed autonomously by wireless device **102** or by the transceiver equipment instructing the wireless device to select a particular cell. The wireless device **102** informs wireless network **104** when it reselects another cell or group of cells, known as a routing area.

[0041] In order to access GPRS services, the wireless device **102** first makes its presence known to wireless network **104** by performing what is known as a GPRS "attach". This operation establishes a logical link between the wireless device **102** and SGSN **126** and makes the wireless device **102** available to receive, for example, pages via SGSN, notifications of incoming GPRS data, or SMS messages over GPRS. In order to send and receive GPRS data, the wireless device **102** assists in activating the packet data address that it wants to use. This operation makes the wireless device **102** known to GGSN **128**; internetworking with external data networks can thereafter commence. User data may be transferred transparently between the wireless device **102** and the external data networks using, for example, encapsulation and tunneling. Data packets are equipped with GPRS-specific protocol information and transferred between wireless device **102** and GGSN **128**.

[0042] Those skilled in the art will appreciate that a wireless network may be connected to other systems, possibly including other networks, not explicitly shown in FIG. **1**. A network will normally be transmitting at very least some sort of paging and system information on an ongoing basis, even if there is no actual packet data exchanged. Although the network consists of many parts, these parts all work together to result in certain behaviours at the wireless link.

[0043] FIG. **2** is a detailed block diagram of a preferred wireless communications device **202**. The wireless device **202** is preferably a two-way communication device having at least voice and advanced data communication capabilities, including the capability to communicate with other computer systems. Depending on the functionality provided by the wireless device **202**, it may be referred to as a data messaging device, a two-way pager, a cellular telephone with data message capabilities, a wireless Internet appliance, or a data communications device (with or without telephony capabilities). The wireless device **202** may communicate with any one of a plurality of fixed transceiver stations **200** within its geographic coverage area.

[0044] The wireless communications device **202** will normally incorporate a communication subsystem **211**, which includes a receiver **212**, a transmitter **214**, and associated components, such as one or more (preferably embedded or internal) antenna elements **216** and **218**, local oscillators (LO's) **213**, and a processing module such as a digital signal processor (DSP) **220**. Communication subsystem **211** is analogous to RF transceiver circuitry **108** and antenna **110** shown in FIG. **1**. As will be apparent to those skilled in the field of communications, the particular design of communication subsystem **211** depends on the communication network in which the wireless device **202** is intended to operate.

[0045] The wireless device **202** may send and receive communication signals over the network after required network registration or activation procedures have been completed. Signals received by antenna **216** through the network are input to receiver **212**, which may perform common receiver functions as signal amplification, frequency down conversion, filtering, channel selection, and the like, and, as shown in the example of FIG. **2**, analog-to-digital (A/D) conversion. A/D conversion of a received signal allows more complex communication functions such as demodulation and decoding to performed in the DSP **220**. In a similar manner, signals to be transmitted are processed, including modulation and encoding, for example, by DSP **220**. These DSP-processed signals are input to transmitter **214** for digital-to-analog (D/A) conversion, frequency up conversion, filtering, amplification and transmission over communication network via antenna **218**. DSP **220** not only processes communication signals, but also provides for receiver and transmitter control. For example, the gains applied to communication signals in receiver **212** and transmitter **214** may be adaptively controlled through automatic gain control algorithms implemented in the DSP **220**.

[0046] Network access is associated with a subscriber or user of the wireless device **202**, and therefore the wireless device requires a Subscriber Identity Module or SIM card **262** to be inserted in a SIM interface **264** in order to operate in the network. SIM **262** includes those features described in relation to FIG. **1**. Wireless device **202** is a battery-powered device so it also includes a battery interface **254** for receiving one or more rechargeable batteries **256**. Such a battery **256** provides electrical power to most if not all electrical circuitry in the device **102**, and battery interface provides for a mechanical and electrical connection for it. The battery interface **254** is coupled to a regulator (not shown) which provides a regulated voltage V to all of the circuitry.

[0047] Wireless communications device **202** includes a microprocessor **238** (which is one implementation of controller **106** of FIG. **1**) which controls overall operation of wireless device **202**. Communication functions, including at least data and voice communications, are performed through communication subsystem **211**. Microprocessor **238** also interacts with additional device subsystems such as a display **222**, a flash memory **224**, a random access memory (RAM) **226**, auxiliary input/output (I/O) subsystems **228**, a serial port **230**, a keyboard **232**, a speaker **234**, a microphone **236**, a short-range communications subsystem **240**, and any other device subsystems generally designated at **242**. Some of the subsystems shown in FIG. **2** perform communication-related functions, whereas other subsystems may provide "resident" or on-board functions. Notably, some subsystems, such as keyboard **232** and display **222**, for example, may be used for both communication-related functions, such as entering a text message for transmission over a communication network, and device-resident functions such as a calculator or task list. Operating system software used by the microprocessor **238** is preferably stored in a persistent (non-volatile) store such as flash memory **224**, which may alternatively be a read-only